


# PBX-9127X

TOP-Level Workstation




## Key applications

- CAD and 3D Modeling
- Product Design and Engineering Simulation
- AI and Deep Learning



Professional Overclocking



Liquid Cooler



Mid Tower Custom Air Flow



PCI 4.0 High Endurance



3 Years Premium warranty

## Basic features



AMD Ryzen™ 9 7950X up to 5.7GHz,  
16 cores / 32 threads



Nvme 1TB Gen4 1DWP, D  
R 700000 - W 400000 IOPS (4KB)



32GB DDR5-5200MHz,  
CAS Latency 39



One or Two Nvidia®GPU supported  
T1000, A2000, 2000ADA, A4000, 4000ADA, A4500\*,  
4500ADA\*, A5500\*, 5500ADA\*, A6000\*, 6000ADA\*



Software di gestione IT da remoto  
Control Center Express



850W Gold + Level Power Supply  
up to 1200W\* Platinum + Level Power Supply



Office Computers Solution srl  
Via Padre Piamarta, 29/d  
25021, Bagnolo Mella (BS) - Italia





Mail: ocs@ocsolution.it  
Mail: supporto.clienti@ocsolution.it  
Telefono: +39 030 266314



# Specifications

Processor
Chipset: X670
Socket: AM5
Processor: AMD Ryzen™ 9 7950X
# of Cores: 16
# of Threads: 32
Core base frequency: 4.50GHz
Core max frequency: Up to 5.7GHz Overclocked
System cooling
Cooling: Water Cooled
Radiator dimensions (mm): 458 (L) x 138 (W) x 38 (H)
Memory
Max configurable memory: 128GB DDR5-5200MHz (4 x 32GB)
CAS latency: 39
Storage
M.2 slots: - 1 x M.2 22110 (PCIe 4.0 x4 mode) - 1 x M.2 2280 (PCIe 4.0 x4 mode) - 1 x M.2 22110 (PCIe 4.0 x4 & SATA mode)
Expansion slots
PCIe slots: - 1 x PCIe 5.0 x16 SafeSlot Core+ - 3 x PCIe 4.0 x16 - 1 x PCIe 3.0 x1
On-Board devices
Connectors: - 2 x USB 3.2 Gen 1 - 1 x USB 3.2 Gen 2 Type-C® - 2 x USB 2.0 - 6 x SATA 6Gb/s - Thunderbolt™ 4
Software
Gestione IT da remoto: Control Center Express

Chassis
Form factor: Midi-Tower
Front panel: Personalized ProXbox's front panel to optimize the cabinet's air flow
Dimensions (mm): 553 (L) x 245 (W) x 502 (H)
Color: Black
Input/Output
Top I/O: - 2 x USB 3.2 Gen 1 - 1 x USB 2.0 - HD audio (Microphone + Audio) - Fan controller - HDD status LED
Rear I/O: - 3 x USB 3.2 Gen 2 (Type-A) - 1 x USB 3.2 Gen 2x2 Type-C® - 4 x USB 3.2 Gen 1 (Type-A) - 2 x USB 2.0 (Type-A) - HDMI port - Display port - 2.5Gb Ethernet - 3 x Jack audio - 1 x Slot M.2 verticale (Key E) - 1 x PS/2
Power supply
Base power: 850W ATX 3.0
Certification:  Gold Level
*Max power (optional or with high level GPUs): 1200W ATX 3.0
Optional Certification:  Platinum Level
Operating system
OS: Microsoft® Windows™ 11 Pro 64 bit
Mouse e tastiera
Mouse: Logitech® B110
Tastiera: Logitech® K120

